


Rough-In Plumbing Measurements



SPECIFICATIONS:

GENERAL SPECIFICATIONS:

| | |
|---------------------|-------------------------|
| Tub Size | 72" x 42" x 24 1/2" |
| | 183 cm x 107 cm x 62 cm |
| Bathing Well | 48" long |
| | 24" wide |
| | 21 1/4" interior depth |
| Maximum Water Depth | 16" |
| Shipping Weight | 134 lbs. / 61 kg |
| Tub Weight Filled | 639 lbs. / 290 kg |
| Tub Only Weight | 81 lbs. / 37 kg |
| Gallons to Overflow | 67 gal. / 55 L |
| Gallons to Operate | 54 gal. / 204 L |

ELECTRICAL SPECIFICATIONS:

| | |
|-------------|---|
| Pump | .80 HP; 5.5 AMP; 110V |
| Requirement | 15 AMP; 110V, separate circuit required protected w/ Class A GFCI |

STANDARD EQUIPMENT:

- 6 Hydrotherapy Jets including:**
- 2 Spinning Back Jets
 - 4 Directional Jets
- Aquatic Quality Features:**
- .80 HP Run-Dry Pump
 - Bath-Side On/Off Air Button
 - "Quiet Pad" Anti-Vibration Pump Mount for Quiet Pump Operation
 - Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
 - 2 Arm Rests
 - Color Matched Trim and Jets (Select Colors)
 - Slip Resistant Floor
 - Durable, Easy to Clean, Lucite® Cast Acrylic Surface
 - Available in 8 Standard No-Charge Colors
- UL & IAPMO Listed, Factory Tested**
Limited 10 Year Warranty

OPTIONAL EQUIPMENT:

- Comfort Pillow--Oval or Rectangle
- Bolt-On Grab Bars
 - White, Biscuit, Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- 1.5 kW Inline Maintenance Heater (Pump Options 1, 2, 3)
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Satin Nickel, Polished Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Satin Nickel, Polished Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- 3-T Integral Tiling Flange, 4-T Integral Tiling Flange
- Optional Pump Location
- Color Matched Acrylic Skirt

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

Fax-On-Demand Document # 1272

